

**REMARKS**

This Preliminary Amendment cancels original claims 1 to 6 in the underlying PCT Application No. PCT/DE03/04250 and adds new claims 7 to 13. The new claims conform the claims to the U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.125, the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including the Title and Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. § 1.121 and § 1.125, a Marked Up Version Of The Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. In the Marked Up Version, underlining indicates added text and "strike-throughs" and double-brackets indicate deleted text. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

Also enclosed is a translated copy of the International Search Report dated May 19, 2004. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is asserted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,  
KENYON & KENYON

Dated: 6/23/2005

By: Richard L. Mayer

Richard L. Mayer  
Reg. No. 22,490

One Broadway  
New York, New York 10004  
Telephone: (212) 425-7200

CUSTOMER NO. 26646

By: Harold C. Deitch  
73,865-  
Harold C. Deitch

[10191/3902]

METHOD AND DEVICE FOR DIAGNOSING THE DYNAMIC CHARACTERISTICS OF  
A LAMBDA SENSOR USED FOR CYLINDER-INDIVIDUAL LAMBDA CLOSED-  
LOOP CONTROL

~~Background of the Invention~~

FIELD OF THE INVENTION

The exemplary embodiment and/or method of the present invention relates to a method and a  
5 device for diagnosing the dynamic characteristics of lambda sensors with respect to a  
cylinder-individual lambda closed-loop control ~~according to the definitions of the species of~~  
~~the individual independent claims.~~

BACKGROUND INFORMATION

For instance, a lambda closed-loop control in conjunction with a catalytic converter is  
10 currently the most effective exhaust-gas treatment method for the spark-ignition engine. Only  
in interaction with currently available ignition and injection systems is it possible to achieve  
very low exhaust values. Limit values for the engine exhaust gas are even mandated by law in  
most countries.

The use of a three-way catalytic converter, or selective catalytic converter, is especially  
15 effective. This type of catalytic converter is able to break down up to more than 98% of  
hydrocarbons, carbon monoxides and nitrogen oxides provided the engine is operated within  
a range of approximately 1% around the stoichiometric air-fuel ratio at  $\lambda = 1$ . In this  
context, lambda specifies the degree to which the actually present air-fuel mixture deviates  
from the  $\lambda = 1$  value, which corresponds to a mass ratio of 14.7 kg air to 1 kg of  
20 gasoline that is theoretically required for complete combustion, i.e., lambda is the quotient of  
the supplied air mass and the theoretical air requirement.

As a general principle, lambda closed-loop control measures the particular exhaust gas, the supplied fuel quantity being immediately corrected according to the measuring result via the injection system, for instance. Used as measuring probe is a lambda sensor, which is able to measure a steady lambda signal around  $\lambda = 1$  and in this way supplies a signal that indicates whether the mixture is richer or leaner than  $\lambda = 1$ .

As ~~is generally~~may be known, the effect of these lambda sensors is based on the principle of a galvanic oxygen concentration cell having a solid state electrolyte.

Furthermore, ~~it is known to utilize~~ a cylinder-individual lambda closed-loop control may be used to improve the exhaust gas if the lambda sensor, owing to its dynamic properties, is able to track lambda fluctuations in the exhaust-gas flow caused by cylinder-individual lambda differences at the installation location of the sensor.

Due to a temporally high-resolution evaluation of the signal coming from the lambda sensor, it is possible to conclude from the composite lambda signal to the lambda of the individual engine cylinders whose exhaust gas is conveyed to the installation location of the sensor. In this way, cylinder-individual lambda differences may be corrected and the exhaust-gas result or, at the very least, the exhaust-gas stability be improved.

The dynamic characteristics of a lambda sensor in new condition is in most cases adequate within a selected operating range. Nevertheless, in the event that the dynamic characteristics of the sensor change, to the effect that cylinder-individual lambda values are unable to be resolved since the response times of the sensor are increasing, the closed-loop lambda control will not intervene although lambda fluctuations are indeed present in the exhaust gas. Causes of a reduced dynamic performance of the sensor are, for instance, constrictions in the protective tube orifices of the sensor or contamination of function-controlling sensor ceramic parts of the solid state electrolyte as a result of deposits. In broad-band sensors, contamination of the diffusion barrier provided there may also play a part. In the worst case, a non-functioning cylinder-individual lambda closed-loop control will result in non-compliance with the mentioned exhaust-gas limit values mandated by law. In this case, the changed dynamic characteristics of the lambda sensor must be indicated by ~~means of~~ a control light, for example.

## SUMMARY OF THE INVENTION

The exemplary embodiment and/or method of the present invention is therefore based on the objective of providing a method and a device of the type mentioned in the introduction, which allow a reliable diagnosis of the dynamic characteristics of a lambda sensor with  
5 respect to a cylinder-individual closed-loop lambda control.

In a method and a device for diagnosis of the aforementioned type this objective is achieved by the features of the respective independent claims.

The method according to the present invention in particular provides that at least one actuating variable of the closed-loop lambda control be detected and compared to a  
10 specifiable maximum threshold, and in the event that the maximum threshold is exceeded, that the dynamic performance of the lambda sensor be considered insufficient with respect to usability for the cylinder-individual closed-loop lambda control.

In a first variant of the exemplary embodiment and/or method of the present invention, the dynamic characteristics of the lambda sensor are detected by the cylinder-individual control  
15 itself. This is based on the thought that the method of operation of individual cylinder-individual controllers diverges when the dynamic properties are insufficient and the associated actuating variables, namely one or more actuating variables, exceed a specifiable maximum threshold value.

In a second variant according to the exemplary embodiment and/or method of the present  
20 invention, the dynamic response of the lambda sensor is detected with the aid of a test function, i.e., by ~~means of~~ an initiated interference or detuning of the instantaneous lambda value. The test function may be implemented on a one-time basis, on an intermittent periodical basis or in an event-triggered manner.

The specifiable maximum threshold for a cylinder-individual controller may be exceeded, for  
25 instance, when the controller is active and the value of the respective actuating variable is higher than the specifiable amount or the actuating variable is unable to be increased further due to its structure. In this case, the dynamic properties of the lambda sensor will be deemed

insufficient with respect to the usability for the cylinder-individual closed-loop lambda control.

Furthermore, the exemplary embodiment and/or method of the present invention relates to a diagnostic device, which operates according to the method of the present invention.

## 5 BRIEF DESCRIPTION OF THE DRAWINGS

The ~~present invention is discussed in greater detail in the following with reference to the included drawing on the basis of an exemplary embodiment from which further features and advantages of the present invention result. The single figure shows a preferred embodiment of the~~Figure shows an exemplary diagnosis method according to the present invention on the  
10 basis of a flow chart.

## DETAILED DESCRIPTION

The following diagnostic routine for detecting the usability or non-usability of a lambda sensor of a spark-ignition engine, which is described in the following with the aid of the figure, ~~is preferably~~may be implemented only during the time when a cylinder-individual  
15 control having individual controllers is active. Depending on the strategy, the test function described hereinafter will be executed once or several times and the results of the tests analyzed only for as long as the test function is active.

Following start 10 of the routine, the engine speed and/or the engine load and/or exhaust-gas mass flow 20 are/is ascertained first. On the basis of these data, it is determined in step 30  
20 whether the engine is in an operating state that is suitable for the cylinder-individual control in the first place, and thus suitable for a detection of the dynamic properties of the lambda sensor. If this is not the case, a return to the beginning of the routine takes place in the form of a loop. In the other case, the actuating variables of the individual controllers are monitored  
40 and, following detection of the actuating variables, it is also checked 50 whether the  
25 amount of at least one of the actuating variables exceeds a specifiable maximum threshold. If this is not the case, a return to step 40 takes place, possibly including a delay.

If one or several actuating variable(s) of the individual controllers exceed(s) a specifiable maximum threshold in its/their amount, it is assumed that the dynamic characteristics of the lambda sensor are insufficient.

5 In a next step 70 it is ascertained whether a suitable instant for activating the test function is present. If this is not the case, this test 70 will be repeated in a loop, possibly also by including a delay stage.

10 Otherwise, the test routine begins in that the instantaneously present values of the actuating variables of the individual controllers are buffer-stored 80. Subsequently, an interference is applied 90 to the instantaneously ascertained lambda values and the actuating variables of the individual controllers monitored or recorded 100.

It is then checked 110 whether the controller(s) is/are able to compensate for the interference. If this is the case, a positive signal will be output 120, if appropriate, to the effect that the dynamic response of the sensor is adequate. Otherwise, it will be assumed that the dynamic requirements are not met and a corresponding negative signal will be output 130.

15 Finally, the interference is reversed 140 and a re-initialization 150 of the individual controllers takes place using the buffer-stored values. Then, another interference is applied, as indicated by return 160.

20 The described procedure or routine is implemented repeatedly, if appropriate, so as to be able to optimize the actuating variables in an iterative manner, so to speak, or in a stepwise manner.

25 The dynamic properties of the lambda sensor with respect to the cylinder-individual control are therefore ascertained with the aid of the controller function itself and/or the described active test function. In a suitable driving situation, the lambda of a cylinder is intentionally detuned by varying the cylinder-individual fuel metering by a previously defined amount x. When the cylinder-individual control is active, this cylinder detuning must be reflected in the associated cylinder-individual actuating variable of the cylinder-individual control as an additional offset of approximately the same magnitude as the detuning. If the resultant change in the actuating variable amounts only to a portion y of the stimulated cylinder detuning, this

indicates that the lambda sensor is no longer able to fully follow the cylinder-individual fluctuations because of a reduced dynamic response. If portion y falls below a specifiable threshold z, i.e., an exhaust-gas relevant residual fault  $x - z$  can no longer be adjusted, a fault signal must be output. The resulting exhaust-gas loss is of no consequence in this case.

- 5 In the case of a satisfactory test result, i.e., the sensor dynamics of the cylinder-individual lambda control are considered adequate since the detuning is completely or virtually completely compensated, the described test function has no detrimental effect on the exhaust gas. In addition, once a test has been concluded, the cylinder detuning will be set back to the initial state, as described.
- 10 It should be noted that a possibly detected change in the dynamic characteristics of the lambda sensor is not relevant for the remaining functions of the engine control that evaluate the lambda sensor signal, and that these must therefore be monitored separately.

The exemplary embodiment and/or method of the present invention may be implemented either as hardware or in the form of a control program as part of the engine control.

~~Summary~~ ABSTRACT OF THE DISCLOSURE

In ~~a~~<sup>A</sup> method for diagnosing the dynamic characteristics of a lambda sensor, which is used at least intermittently for a cylinder-individual lambda closed-loop control, ~~the present invention~~<sup>which</sup> provides for at least one actuating variable of the lambda closed-loop control to be detected and compared to a specifiable maximum threshold, and, if the maximum threshold is exceeded, the dynamic response of the lambda sensor is deemed insufficient with respect to the usability for the cylinder-individual lambda closed-loop control.